

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1 to 27 in the underlying PCT Application No. PCT/EP03/02465 and adds new claims 28 to 56.. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/EP03/02465 includes an International Search Report, dated July 3, 2003, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.

It is respectfully submitted that the subject matter of the present application is new, non-obvious and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON

Dated: October 7, 2004

By:



Clifford A. Ulrich
Reg. No. 42,194

One Broadway
New York, New York 10004
(212) 425-7200
CUSTOMER NO. 26646

CONVERTER SYSTEM, METHOD, AND CONVERTER

~~Background of the Invention~~FIELD OF THE INVENTION

The present invention relates to a converter system, method, and a converter.

BACKGROUND INFORMATION

Certain converters ~~Converters~~ for powering electric motors are well-known conventional. In this context, an intermediate circuit voltage provided for powering an inverter is mostly generated from an a.c. network voltage, using a rectifier. During regenerative operation, the energy generated is consumed by a braking resistor, which is supplied current by a brake chopper, i.e., an electronic circuit breaker. The heat generated at the braking resistor must be dissipated, for which appropriate space is provided, in particular for air flow, as well. In addition, a converter is necessary for each electric motor.

SUMMARY

~~According to an example embodiment~~ Therefore, the object of the present invention ~~is to provide,~~ an option is provided for powering a plurality of electric motors in a cost-effective manner, ~~the intention also being that the means for attaining the object be designed to be as compact as possible and~~ compact manner.

In the case of an adapter device, the converter system, ~~the object of the present invention is achieved according to the features specified in Claim 1 or Claim 21, in the case of the method, the object of the present invention is achieved according to the features specified in Claim 24, and in the~~

~~case of the converter, the object of the present invention is achieved according to the features specified in Claim 27.~~

~~In the case of the adapter device, the essential features of the present invention are that the converter system includes~~

5 ~~[[-]] includes: at least one supply module, which provides a unipolar, intermediate circuit voltage; [[-]] one or more drive modules, which may be powered by the intermediate circuit voltage and each include at least one inverter for~~
10 ~~powering at least one electric motor, in particular e.g., a synchronous motor or an asynchronous motor; and [[-]] at least one buffer module for storing energy.~~

~~In this context, it is advantageous~~ It may be provided that
15 ~~the buffer module allows energy generated by the drive modules during regenerative operation to be temporarily stored. In particular, the buffer module may be supplied with energy for periods of time, especially e.g., during regenerative operation of at least one drive module, and stored energy may~~
20 ~~be subsequently released by the buffer module to at least the drive modules. The modular construction is~~ may provide a further advantage, for in the case of the converter system, the modules are combined according to the application, and therefore, the variety or number of components ~~is~~ may be
25 ~~reduced in comparison with a system made of separate converters. Modules in regenerative operation and modules in motive operation are connected by the intermediate circuit and may therefore balance out~~ or equalize energy mutually. In addition, the buffer module does not load the network, because
30 ~~current is only fed to the capacitor of the buffer module when a first critical value of the intermediate circuit voltage is exceeded. Thus, current is supplied in a controlled manner.~~

~~In a preferred variant~~ an example embodiment, at least one
35 ~~supply module includes a rectifier for generating d.c. voltage from an a.c. voltage, in particular e.g., from a three-phase~~

a.c. network voltage. In this context, it ~~is advantageous~~ may be provided that the converter system may be powered by a customary conventional industrial or domestic a.c. voltage network.

5

In ~~a preferred variant~~ an example embodiment, at least one supply module includes a feedback unit, or a feedback unit is connectible as a module to the intermediate circuit voltage and the a.c. voltage, ~~in particular e.g.,~~ to a three-phase a.c. network voltage, to provide feedback or to feed energy back from the intermediate circuit into the network. In this context, it ~~is advantageous~~ may be provided that energy, which is generated during regenerative operation and ~~cannot~~ may not be stored by the buffer module, may be fed back into the network. Therefore, the energy costs may be reduced.

10

15

In ~~a preferred variant~~ an example embodiment, at least one supply module includes an electronic circuit breaker, which allows passage of or blocks current induced by the intermediate circuit voltage and in the direction of a device connected to an output of the supply module, as a function of the activation of the electronic circuit breaker. In this context, it ~~is advantageous~~ may be provided that the electronic circuit breaker may be used to control the current for a braking resistor and/or for a buffer module and therefore releases energy to the buffer module as a function of the intermediate circuit voltage.

20

25

In ~~a preferred variant~~ an example embodiment, the drive circuit of the electronic circuit breaker is connected to a means device for measuring the intermediate circuit voltage. In this context, it ~~is advantageous~~ may be provided that the activation may be designed to be a function of the intermediate circuit voltage, ~~in particular e.g.,~~ that the switching or a pulsed operating mode of the switch may

30

35

therefore be implemented in response to critical values being exceeded.

In ~~a preferred variant~~ an example embodiment, the buffer

5 module includes a capacitor, of which the capacitance is greater than the sum of that of all the capacitors to which the intermediate circuit voltage is directly applied. In this context, ~~it should be pointed out that~~ the capacitor of the buffer module ~~is~~ may not be directly connected to the
10 intermediate circuit, but via further devices, such as diodes. In the case of this value of the capacitance, it ~~is~~ advantageous may be provided that a braking resistor having high temperatures and requiring a large unit volume, ~~in particular e.g.,~~ for cooling, may be ~~dispensed with~~
15 eliminated. In addition, the energy is not subsequently converted into heat but retained by capacitors of the buffer module in the form of electrical energy, which may be fed back to the drive modules connected to the intermediate circuit. Consequently, the energy consumption ~~is~~ may be decreased, and
20 the energy costs ~~are~~ may be reduced.

In ~~a preferred variant~~ an example embodiment, the buffer

module includes a capacitor, of which the capacitance is dimensioned so that during motive operation at nominal load,
25 with the capacitor directly connected to the intermediate circuit, the a.c. voltage component of the intermediate circuit voltage ~~would~~ may be less than half as large as the a.c. voltage component with the capacitor not connected in this manner. This characteristic is only used for defining
30 the value of the capacitance of the capacitor. In ~~the variant according to~~ an example embodiment of the present invention, the capacitor of the buffer module is not directly connected to the intermediate circuit, for it is charged or discharged by further devices, as a function of the intermediate circuit
35 voltage. In the case of this sizing, it ~~is advantageous~~ may

be provided that the buffer module may be designed to have a capacitor, of which the unit volume is small in relation to the sum of the volumes of the intermediate circuit capacitors of the separate converters corresponding to the converter system. In particular, a more cost-effective foil or film capacitor may be used. Thus, the unit volume of the overall converter system ~~is~~ may be low, and, all in all, the converter system may be inexpensively manufactured, ~~in particular e.g.,~~ when using a supply module having feedback.

In ~~a preferred variant~~ an example embodiment, a buffer module is provided, which is connected to an output of the supply module and includes a capacitor, of which the charging current may be influenced and/or controlled by at least the electronic circuit breaker. In this context, it ~~is advantageous~~ may be provided that the capacitor may be sized according to the application, and that energy from the capacitor may be fed back to drive modules or optionally to a supply module containing a network feedback unit.

In ~~a preferred variant~~ an example embodiment, buffer module PM includes at least one electrolytic capacitor. In this context, it ~~is advantageous~~ may be provided that the buffer module may be provided with high capacitances.

In the case of the converter system, ~~the essential features of the present invention are that,~~ to form the converter system: ~~[[, -]]~~ at least one supply module, which provides a unipolar, intermediate circuit voltage; ~~[[-]]~~ one or more drive modules, which may be powered by the intermediate circuit voltage and each include at least one inverter for powering at least one electric motor, ~~in particular e.g.,~~ a synchronous motor or an asynchronous motor; and ~~[[-]]~~ at least one buffer module for storing energy are at least electrically connectible via a bus system, the bus system including: ~~[[-]]~~

at least two power cables (+,-) for carrying the intermediate circuit voltage; and [[-]] a power cable BRC for electrically connecting the supply module(s) to the buffer module(s).

5 In this context, it ~~is advantageous~~ may be provided that the bus system may be configured so that different modules are connectible and connected to the intermediate circuit voltage for removing energy or supplying energy to the intermediate circuit.

10 In ~~a preferred variant~~ an example embodiment, the modules, such as the buffer module or drive modules, the supply module, and, if applicable, further modules each have the same kind of interface for electrical and mechanical connection to the bus system. In particular, the interface is constructed in the same manner in all of the modules. In this context, it ~~is advantageous~~ may be provided that a system is provided which is highly flexible and may be adapted to the specific applications. For example, a feedback module may be added to 15 an existing converter system, in order to save energy, or a buffer module or a larger buffer module may be connected. In addition, different drive modules may be connected.

25 In the case of the method, ~~the essential features of the present invention are that~~, in order to operate a buffer module in a converter system including: [[-]] at least one supply module VM, which provides a unipolar, intermediate circuit voltage; [[, -]] one or more drive modules AM, which may be powered from the intermediate circuit voltage and each include at least one inverter for powering at least one electric motor; and [[-]] at least one buffer module PM for storing energy, ~~where~~ [[-]] the intermediate circuit voltage is measured; and [[-]] in response to a first critical value of the intermediate circuit voltage being exceeded, buffer 30 module PM is supplied with energy, when the overall regenerative power of first drive modules exceeds the motive

power of second drive modules; the buffer module feeds back energy to the modules powered by the intermediate circuit voltage, when the total motive power of drive modules exceeds the regenerative power. In this context, it ~~is advantageous~~
5 may be provided that the intermediate circuit voltage is monitored, several drive modules being connected which may transmit energy via the intermediate circuit. Thus, the number of cases in which the intermediate circuit voltage exceeds a critical value ~~is~~ may be reduced. In addition, a
10 single buffer module, which may be selected to be smaller than the sum of the capacitances of the intermediate circuit capacitors of corresponding, separate converters when appropriately dimensioned, may be used for several drive modules in this manner. This ~~reduces~~ may reduce the costs and
15 the unit volume. Moreover, a single circuit breaker ~~is~~ may be sufficient for switching, and it ~~is~~ may be sufficient to measure the intermediate circuit voltage only once for several drive modules.

20 In the case of a second critical value of the intermediate circuit voltage being exceeded, ~~a preferred variant~~ an example embodiment provides for current to flow through a braking resistor to dissipate energy, when the total regenerative power of first drive modules exceeds the motive power of
25 second drive modules. In this context, it ~~is advantageous~~ may be provided that, in a corresponding application case, the converter system may additionally be provided with a module that includes a braking resistor, and that the intermediate circuit voltage may therefore be kept in the permissible
30 range. In this connection, the critical value for the switching of the braking resistor may be designed to be different from the critical value for the switching of the buffer capacitor. Therefore, ~~in a particularly advantageous manner,~~ energy may be stored in the buffer module in the case
35 of short-term regenerative operation, and consumed in the

braking resistor in the case of long-term regenerative operation.

In ~~another preferred variant~~ an example embodiment, the second
5 and first critical values are identical. In this context, it
~~is advantageous~~ may be provided that the method may be
implemented in a ~~particularly simple manner.~~ simple manner.

~~Further advantageous developments are yielded from the~~
10 ~~dependent claims.~~ According to an example embodiment of the
present invention, a converter system includes: at least one
supply module configured to provide a unipolar, intermediate
circuit voltage; at least one drive module powerable by the
intermediate circuit voltage, each drive module including at
15 least one inverter configured to power at least one electric
motor; and at least one buffer module configured to store
energy.

~~List of Reference Numerals~~ According to an example embodiment
20 of the present invention, a converter system includes: at
least one supply module configured to provide a unipolar,
intermediate circuit voltage; at least one drive module
powerable by the intermediate circuit voltage, each drive
module including at least one inverter configured to power at
25 least one electric motor; at least one buffer module
configured to store energy; and a bus system configured to
electrically connect the supply module, the drive module and
the buffer module, the bus system including at least two power
cables configured to carry the intermediate circuit voltage
30 and a power cable configured to electrically connect the
supply module to the buffer module.

According to an example embodiment of the present invention, a
method for operating a buffer module in a converter system,

the converter system including at least one supply module configured to provide a unipolar, intermediate circuit voltage, at least one drive module powerable from the intermediate circuit voltage and including at least one inverter configured to power at least one electric motor, and at least one buffer module configured to store energy, includes: measuring the intermediate circuit voltage; in response to the intermediate circuit voltage exceeding a first critical value, supplying the buffer module with energy when an overall regenerative power of a first drive module exceeds a motive power of a second drive module; and feeding back energy by the buffer module to drive modules powered by the intermediate circuit voltage when a total motive power of the drive modules exceeds the regenerative power.

According to an example embodiment of the present invention, a converter includes: a rectifier configured to generate an intermediate circuit voltage; an inverter configured to be powered by the intermediate circuit voltage; a first capacitor not directly connected to the intermediate circuit voltage configured to be energized by an electronic circuit breaker in a controlled manner as a function of the intermediate circuit voltage, the first capacitor configured to release energy to an intermediate circuit; and a second capacitor directly connected to the intermediate circuit voltage, a capacitance of the first capacitor and a capacitance of the second capacitor configured so that during motive operation at nominal load, with the capacitor directly connected to the intermediate circuit, an a.c. voltage component of the intermediate circuit voltage is less than half an a.c. voltage component with the first capacitor removed.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 schematically illustrates a converter system.

Figure 2 schematically illustrates a converter system having two drive modules.

Figure 3 schematically illustrates an integrated buffer/supply module.

LIST OF REFERENCE NUMERALS

VM	supply module
AM	drive module
PM	buffer module
PVM	integrated buffer/supply module
M	electric motor
BRC	electrical connecting point
1	rectifier
2,23	means <u>device</u> for measuring voltage
3	drive circuit
10	charging means <u>device</u>
32	drive circuit
33	means <u>device</u> for measuring current
C1	capacitor
C2	capacitor
C3	capacitor
D1,D2,D3	diodes
T1,T2	electronic circuit breaker

~~The present invention shall now be explained in detail with reference to the figures.~~

DETAILED DESCRIPTION

~~Shown~~ Illustrated in Figure 1 is a converter system of an example embodiment of the present invention, where a supply module VM ~~contains~~ includes a rectifier 1, which generates an intermediate circuit voltage (reference symbols +, -) from a

three-phase a.c. network voltage, i.e., three-phase voltage, a capacitor C1 being provided for reducing electromagnetic interference. The intermediate circuit voltage is directly applied to capacitor C1.

5

Means Device 2 for measuring voltage ~~are~~ is connected to drive circuit 3 of electronic circuit breaker T1, which may therefore be reset from the blocked state into the conductive state in response to the intermediate circuit voltage exceeding a critical value. Capacitor C2 may be charged via this electronic circuit breaker T1.

Intermediate circuit voltage (+, -) also powers drive modules AM, which each include converters for powering electric motors, ~~in particular e.g.,~~ asynchronous motors or synchronous motors. Also integrated into drive modules AM are electronic circuits, which are used for implementing open-loop and/or closed-loop control methods. Therefore, drive modules AM are ~~essentially like~~ similar to converters, except for rectification and intermediate circuit capacitor C1. In addition, the buffer module and, if indicated, further modules, such as the feedback module or a module containing a braking resistor, are also not in the drive module.

Capacitor C2 is charged and the maximum charging current is therefore limited via charging ~~means device~~ 10, which, ~~in a first exemplary embodiment of the present invention,~~ may be implemented as an electrical resistor.

In other exemplary embodiments of the present invention, inductive elements or combinations of inductive elements and electrical resistors are provided as charging ~~means device~~ 10.

The capacitance of capacitor C1 is selected to be so low that, during rated, motive operation, and in the case of a disconnected buffer module, the alternating component of the

intermediate circuit voltage is ~~essentially~~ substantially equal to the alternating component that would be present if capacitor C1 were not present. The capacitor C1 is not implemented in the form of an electrolytic capacitor, but may
5 be implemented as, e.g., a foil or film capacitor. In the case of a connected buffer module in rated operation, the alternating component of the intermediate circuit voltage ~~essentially~~ substantially does not change, as long as all of the drive modules are in motive operation. Only when the
10 intermediate circuit voltage exceeds a first critical value as a result of regenerative operation, is the buffer module charged with energy and the energy fed back into the intermediate circuit after the end of regenerative operation. In the case of a 400 V three-phase network ~~customary in~~
15 ~~industry,~~ , which may be conventional, this value is over 600 V, e.g. ~~advantageously,~~ 800 V or more.

Capacitor C2 is designed as an electrolytic capacitor. The magnitude of its capacitance is such that, in the event of
20 capacitor C1 being replaced by C2, the intermediate circuit voltage ~~would~~ may be smoothed out ~~in such a manner,~~ that the alternating component ~~would~~ may be less than half as large as in the aforementioned case. However, this direct connection with the intermediate circuit ~~would~~ may load the network,
25 since large charging currents are generated in the case of an uncharged capacitor. In particular, it ~~would~~ may then also be necessary to limit the charging current, e.g., with the aid of a charging resistor. In the present exemplary embodiment of the present invention, capacitor C2 is not directly connected
30 to the intermediate circuit voltage, but only indirectly connected to it via further devices, such as via charging means device 10 and the electronic circuit breaker. In ~~other~~ specific example embodiments of the present invention, capacitor C2 is connected to the intermediate circuit voltage
35 by other or further means device(s), but never directly.

In the exemplary embodiment ~~according to~~ illustrated in Figure 1, the capacitor is supplied with energy in regenerative operation, when the intermediate circuit voltage has exceeded a critical value. When several drive modules are connected, there are operating states in which a portion of the drive modules are regeneratively operated and another portion motively operated. ~~Of course, it is~~ It may be important whether on the whole, energy is supplied to the intermediate circuit, i.e., the intermediate circuit voltage increases, or energy is removed from the intermediate circuit.

In Figure 1, the electrical connecting point is denoted by reference symbol BRC. Buffer module PM having charging ~~means~~ device 10 is connected to this.

Diode D1 has the function of protecting the components, in particular e.g., electronic circuit breaker T1, diode D1 acting as a freewheeling diode for charging ~~means~~ device 10. Diode D2 allows the stored energy of capacitor C2 to be released to the intermediate circuit while it discharges, in that current flows through diode D2.

A converter system of an example embodiment of the present invention having two drive modules is ~~shown~~ illustrated in Figure 2. The intermediate circuit, including the two lines + and - for the intermediate circuit voltage and line BRC for conducting buffer current through to the buffer module, is ~~designed~~ arranged as a bus system to which the drive modules are connected by their respective interfaces.

Therefore, to form the converter system, ~~[[-]]~~ at least one supply module VM, which provides a unipolar, intermediate circuit voltage, ~~[[-]]~~ one or more drive modules AM, which may be powered by the intermediate circuit voltage and each include at least one inverter for powering at least one

electric motor, ~~in particular e.g.,~~ a synchronous motor or an asynchronous motor, and ~~[[-]]~~ at least one buffer module PM for storing energy may be electrically and mechanically connected via the bus system, the bus system including: ~~[[-]]~~ at least two power cables (+, -) for carrying the intermediate circuit voltage; and ~~[[-]]~~ a power cable BRC for electrically connecting the supply module(s) to the buffer module(s).

In this context, the bus system ~~is advantageously~~ may be implementable as a rail system, into which modules are insertable. To that end, the modules, such as buffer module PM or buffer modules, drive modules AM, supply module VM, and, if applicable, further modules each have an interface for electrical and mechanical connection to the bus system. In particular, this interface ~~is~~ may be constructed in the same manner in all of the modules. Instead of a rail system, bus systems operating in the same manner may also be used. However, a bus system, which is suitably constructed for receiving the above-mentioned and, in each case, the identically stamped interface at various discrete positions or even an infinite number of positions, may be used ~~in a considerably advantageous manner.~~

~~In a further~~ In an exemplary embodiment of the present invention, the supply module may include a network feedback unit. In ~~another~~ an exemplary embodiment of the present invention, the network feedback unit may also be constructed as an independent module having, ~~in turn,~~ the same kind of interface for connection to the bus system.

In particular, the method of an example embodiment of the present invention for directing energy from the intermediate circuit to a capacitor having a large capacitance may also be realized with the aid of a single converter.

~~Shown~~ Illustrated in Figure 3 is an integrated buffer/supply module PVM, in which the characteristics of supply module VM and buffer module PM are included. In addition, further ~~advantageous~~ characteristics are realized in this integration:

Means A device 23 for measuring the intermediate circuit voltage and ~~means~~ a device for measuring the intermediate circuit current 33 are connected to drive circuit 3 for electronic circuit breaker T1. Therefore, the intermediate circuit current may also be considered during the triggering of electronic circuit breaker T1. In particular, a value of the loading of electronic circuit breaker T1 is ascertainable from these measured values of intermediate circuit voltage and intermediate circuit current, and the electronic circuit breaker may therefore be protected from overload. A further ~~advantageous~~ result of this is that inductor 10 may be sized to be the smaller, because the maximum expected currents for inductor 10 may be co-determined by switch T1.

The determination of the intermediate circuit current is also used for another purpose, ~~namely~~ e.g., for the overload protection of buffer/supply module PVM, i.e. ~~in particular,~~ for example, for the supply module part and the charging of the buffer.

Capacitor C3 is ~~designed~~ arranged as an intermediate circuit capacitor. In ~~further~~ exemplary embodiments of the present invention, it may be implemented, ~~in particular~~ e.g., as a cost-effective film capacitor and not as an electrolytic capacitor.

During regenerative operation, the intermediate circuit voltage increases until the voltage threshold value of drive circuit 3 is reached. When this value is exceeded, the electronic circuit breaker is reset to the conductive state by drive circuit 3. Therefore, the current for charging

capacitor C2 flows through inductor 10 and is measured by ~~means device~~ for measuring intermediate circuit current 33.

If the current value determined in this manner reaches a critical value, electronic circuit breaker T1 is switched off.

5 The charging current for capacitor C2 then continues to flow through inductor 10 and freewheeling diode D1 until the energy of the coil has ~~essentially~~ substantially gone over to the capacitor. During the described charging cycle, the intermediate circuit voltage decreases a little until
10 electronic circuit breaker T1 is switched off. After the switching-off point, the intermediate circuit voltage increases again and the described charging cycle is repeated.

~~Means A device~~ for measuring voltage 23 ~~provide~~ provides a
15 second, further stepped-down value, which is a function of the intermediate circuit voltage and is transmitted to drive circuit 32 of electronic circuit breaker T2. At their inputs, drive circuits 3 and 32 have the same threshold voltage values, as a function of which electronic circuit breakers T1
20 and T2 are activated. This allows the buffer capacitor, i.e., capacitor C2, to initially be charged in a simple manner, and then allows the electronic circuit breaker to be switched into a conductive state only in response to a further increase in the intermediate circuit voltage, so that intermediate circuit
25 current is drawn off by braking resistor BRC. Consequently, the braking resistor connected to outer terminals BRC may be supplied with energy as a function of the intermediate circuit voltage. A freewheeling diode D3 is connected in parallel with braking resistor BRC, since as a result, braking
30 resistors, which have leads and have not only ohmic components but also inductive components, may also be used.

In ~~further~~ exemplary embodiments of the present invention, buffer/supply module PVM is ~~designed~~ arranged so that
35 terminals BRC are integrated and the braking resistor is ~~likewise~~ situated in the interior of buffer/supply module PVM.

~~Abstract~~

ABSTRACT

5 A converter system and method, including: ~~[[-]]~~ at least one supply module ~~[[VM]]~~, which provides a unipolar, intermediate circuit voltage; ~~[[-]]~~ one or more drive modules ~~[[AM]]~~, which may be powered from the intermediate circuit voltage and each include at least one inverter for powering at least one electric motor; and ~~[[-]]~~ at least one buffer module ~~[[PM]]~~ for storing energy.